




With our Solex™ laminate solutions, Deceuninck offers faux wood laminates and a large selection of solid color options. Combine interior color preference with heat-reflective exterior laminate for curb appeal and unrivaled quality, color retention and weather resistance.



An advanced material developed through an intensive manufacturing process and formulated to withstand the harsh effects of weather and ultraviolet light.

Sunshield® is an environmentally minded compound that exceeds all required material standards for strength and best-in-class performance.



Available with Innergy® Rigid Thermal Reinforcements, the next generation of reinforcements designed to slide easily into window chambers for great support and thermal performance.

Innergy® Rigid Thermal Reinforcements are advanced fiber glass reinforced resin inserts with all the strength and structural reinforcement of aluminum, but with a whole new set of high-performance benefits.

deceuninck



deceuninck | BUILDING A SUSTAINABLE HOME

140 Series

HIGH PERFORMANCE WINDOW SYSTEM

deceuninckna.com



For more information, call 877-563-4251 or email dna.info@deceuninck.com
www.DeceuninckNA.com



The name and logo of Deceuninck, of its affiliated companies and of the products and services manufactured by them, are trademarks and trade names protected by national and international laws.

©2023 Deceuninck North America. All rights reserved.

Part No. FEN-130-0323



A NEW REALM OF POSSIBILITY

The 140 Series windows open a window of opportunity through high-end window design.

With polished design and the added flexibility of multiple configuration options, these windows are built to exceed performance requirements for impact resistance and energy savings requirements for the ENERGY STAR program.

Designed to complement existing Deceuninck window and door systems, the 140 Series adds the freedom of a casement window for increased ventilation and a wider opening.

PEAK PERFORMANCE

The 140 Series is a high-performance window system, with enhanced structural and thermal performance for use in renovation and remodeling, and new construction applications.

- Rich, contemporary look
- Premium performance: up to DP50
- High-end glass options

CONFIGURATIONS

- Casement
- Awning
- Picture Window

STANDARD SOLID COLORS



White



Sandstone



Clay

STANDARD LAMINATE COLORS



Lt Oak



Dark Oak



Natl Cherry



Cherry



Winchester Lt Oak



Natl Maple



Midnight



Wicker



Bronze



Choc Brown



Metallic

** Consult your Deceuninck sales representative for details on colors included in the stocked color and laminate offering and related lead times. Lead times for colors may vary based on the color selected.*



LEARN MORE



CASEMENT/AWNING

- Fully welded frame and sash
- New construction or replacement applications
- Triple-seal design
- Compatible with standard window hardware
- Screw bosses and tic marks for easy hardware location
- Water channels designed to direct wind-driven rain away from window

PERFORMANCE*

- Structural: Up to DP50
- Thermal performance range: .19 to .42
- Impact capable

DESIGN

- Frame: 3 1/4"
- IG options: Up to 7/8"
- Compatible with Deceuninck Group IV accessories
- Multi-chamber frame for improved energy efficiency
- Designed for Innergy® reinforcements

** Actual performance varies by window configuration and glass package.*

