




With our Solex™ laminate solutions, Deceuninck offers faux wood laminates and a large selection of solid color options. Combine interior color preference with heat-reflective exterior laminate for curb appeal and unrivaled quality, color retention and weather resistance.



An advanced material developed through an intensive manufacturing process and formulated to withstand the harsh effects of weather and ultraviolet light.

Sunshield® is an environmentally minded compound that exceeds all required material standards for strength and best-in-class performance.



Available with Innergy® Rigid Thermal Reinforcements, the next generation of reinforcements designed to slide easily into window chambers for great support and thermal performance.

Innergy® Rigid Thermal Reinforcements are advanced fiber glass reinforced resin inserts with all the strength and structural reinforcement of aluminum, but with a whole new set of high-performance benefits.

deceuninck



deceuninck | BUILDING A SUSTAINABLE HOME

279 Series

HIGH PERFORMANCE WINDOW SYSTEM

deceuninckna.com



For more information, call 877-563-4251 or email dna.info@deceuninck.com
www.DeceuninckNA.com



The name and logo of Deceuninck, of its affiliated companies and of the products and services manufactured by them, are trademarks and trade names protected by national and international laws.

©2023 Deceuninck North America. All rights reserved.

Part No. FEN-131-0323



A VISION OF EXCELLENCE

The 279 Series windows from Deceuninck represent a high-end and highly technical approach to window design.

These beautiful window systems incorporate unsurpassed innovation and engineering technology to exceed performance requirements for impact resistance and standard ENERGY STAR requirements.

Select from a variety of highly durable, low-maintenance colors and optional finishes. Create your own unique window by including popular options such as ultra-performance insulated glass, simulated divided lites or mini-blinds hermetically sealed inside the glass.

PERFORMS WITH STYLE

The 279 Series is a high-performance window system, with enhanced structural and thermal performance for use in renovation and remodeling, and new construction applications.

- Rich, contemporary look
- Premium performance: up to DP50
- High-end glass options
- Latest integrated locking and latching hardware
- Magnetic seal

CONFIGURATIONS

- Double Hung
- Horizontal Slider
- Picture Window

STANDARD SOLID COLORS




STANDARD LAMINATE COLORS



* Consult your Deceuninck sales representative for details on colors included in the stocked color and laminate offering and related lead times. Lead times for colors may vary based on the color selected.



LEARN MORE



¾" - 1" IG THICKNESS RANGE

- Accommodate integral blinds

SIMULATED DIVIDED LITE (SDL) COMPATIBLE

RECESSED LOCK AND KEEPER INTEGRATED LOCK-AND-TILT LATCH OPTION

TRIPLE WEATHER-STRIPPING AT ALL SEALING LOCATIONS

BULB SEAL COMPRESSION AT HEAD AND SILL

- "Dual bulb" at sill



PERFORMANCE*

- Structural: Up to DP50
- Thermal performance range: .19 to .48
- Impact capable
- Designed to achieve excellent Sound Transmission Coefficient (STC)

DESIGN

- Low profile design to maximize viewing area
- Capable of using up to 1" IG provides improved thermal performance and reduces outside sound
- 3¼" frame depth increases structural rigidity for a lifetime of performance
- Built in J-Channel to accept vinyl siding
- High-end glass options including tempered, laminated and triple glazing
- Optional integrated lock/tilt mechanism
- Rounded contours and soft corners improve the adhesion of lamination and painting
- Compatible with Deceuninck Group IV accessories
- Low-profile, edge-located accessory groove with more than 100 accessories allow for all types of installations
- Designed for Innergy reinforcements
- Equal Lite and Unequal Lite sash options
- Multi-chamber frame for improved energy efficiency
- Multiple weather seal locations

* Actual performance varies by window configuration and glass package.

