




With our Solex™ laminate solutions, Deceuninck offers real and faux wood laminates and a large selection of solid color options. Combine interior color preference with heat-reflective exterior laminate for curb appeal and unrivaled quality, color retention and weather resistance.



An advanced material developed through an intensive manufacturing process and formulated to withstand the harsh effects of weather and ultraviolet light.

Sunshield® is an environmentally minded compound that exceeds all required material standards for strength.



Available with Innergy® Rigid Thermal Reinforcements, the next generation of reinforcements designed to slide easily into window chambers for great support and thermal performance.

Innergy® Rigid Thermal Reinforcements are advanced fiber glass reinforced resin inserts with all the strength and structural reinforcement of aluminum, but with a whole new set of high-performance benefits.



The name and logo of Deceuninck, of its affiliated companies and of the products and services manufactured by them, are trademarks and trade names protected by national and international laws.

©2020 Deceuninck North America All rights reserved.

Part No. FEN-133-1119



441.720 WINDOW SYSTEM



www.DeceuninckNA.com



441.720
WINDOW SYSTEM



Offered with and without integral nail fin

Compatible with Deceuninck Group V accessories

Integral accessory groove to receive Deceuninck's installation and trim accessories

Placement of internal cavities optimized for thermal performance

Rounded edges for ease of painting and lamination

3/4" through 1 1/4" IG dual and triple glazing options

Triple weather seal locations

INNERGY® Thermal Reinforcements

The Dawn of Affordable Energy Efficiency

Innovation meets performance in the beauty and distinctive design of the **eos**® line of high-efficiency windows from Deceuninck.

eos applies world-class engineering and advanced material science to set a higher standard for window performance, economy and fabricator efficiency.

The **eos** window system offers a variety of color and finish options including exterior and interior laminate colors.

STANDARD SOLID COLORS



STANDARD LAMINATE COLORS



*Consult your Deceuninck sales representative for details on colors, laminate offering and related lead times. Lead times for colors may vary based on the color selected.

Most Efficient Window

eos is designed to meet the criteria for ENERGY STAR 6.0 as well as its "Most Efficient 2020" designation by outperforming standard ENERGY STAR requirements.

Various glass packages from 3/4" to 1 1/4" can be accommodated.

eos is designed to accept Deceuninck's full line of Group V accessories.

CONFIGURATIONS

- Casement
- Awning
- Picture Window

CASEMENT/AWNING

- Fully welded frame and sash
- New construction and replacement applications
- Triple weather seal locations
- Compatible with standard window hardware
- Screw bosses at hardware mounting locations
- Water channels designed to direct wind-driven rain away from window
- 3 1/4" frame

PERFORMANCE*

- Structural: Up to DP 50
- Thermal performance range: .42 to .19
- Impact capable

DESIGN

- Frame: 3 1/4"
- 3/4" through 1 1/4" IG dual and triple glazing options
- Compatible with Deceuninck Group V accessories
- Multi-chamber frame for improved energy efficiency
- Designed for Innergy® reinforcements

*Actual performance varies by window configuration and glass package